

检验检测报告



报告编号: 6260819087

第 1 页, 共 13 页

客户信息	委托单位: 江苏苏美达伊顿纪德品牌管理有限公司/江苏苏美达伊顿纪德品牌管理有限公司南京六合分公司/江苏苏美达伊顿纪德管理咨询有限公司上海长宁分公司/江苏苏美达伊顿纪德管理咨询有限公司上海分公司/江苏苏美达伊顿纪德品牌管理有限公司上海分公司 委托地址: ----- 生产单位: ----- 生产地址: -----				
客户认定信息	样品名称: 学院多功能防寒服 型号/规格/等级: ----- 样品编号/批号: ----- 样品数量: 4 件 商标: ETON KIDD 颜色: 灰蓝 其他: 外皮: 面料-聚酯纤维: 100%; 里料-聚酯纤维: 100%; 内胆: 面料-锦纶: 100%; 里料-锦纶: 100%; 填充物-聚酯纤维: 100%				
检验类别	委托检验	样品受理/测试开始日期	2026-08-19	报告签发日期	2026-08-25
判定依据	GB 18401-2010 《国家纺织产品基本安全技术规范》(B 类) GB 31701-2015 《婴幼儿及儿童纺织产品安全技术规范》(B 类) GB/T 29862-2013 《纺织品 纤维含量的标识》 GB/T 31888-2015 《中小学生校服》				



检验检测报告



报告编号: 6260819087

第 2 页, 共 13 页

综合检验结论	见附页
备注	本报告中检验检测项目均在相应的标准规定环境下进行。

批准人:

尹晓娇

签名:

尹晓娇



检验检测报告

报告编号: 6260819087

第 3 页, 共 13 页

测试项目(学院多功能防寒服)	判定依据	结论
[内胆]		
纤维含量	GB/T 29862-2013 GB/T 31888-2015	合格
异味	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
水洗尺寸变化率	GB/T 31888-2015	合格
水洗后扭曲率	GB/T 31888-2015	合格
水洗后外观	GB/T 31888-2015	合格
[内胆-领口里料]		
pH 值	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
甲醛含量	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
[内胆-面料]		
pH 值	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
甲醛含量	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
可分解致癌芳香胺染料	GB 31701-2015(B 类)	合格
耐摩擦色牢度	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
耐汗渍色牢度	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
耐水色牢度	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
耐皂洗色牢度	GB/T 31888-2015	合格



深检(上海)质量技术服务有限公司

SMQ(Shanghai) Quality Technology Service Co., Ltd

地址: 上海市闵行区都园路 2060 号 5 幢 3 楼 312-322 室 电话: 021-52265739

Address: Room 312-322, 3rd Floor, Building 5, 2060 Duyuan Road, Minhang District, Shanghai

扫描下载报告辨真伪



检验检测报告

报告编号: 6260819087

第 4 页, 共 13 页

测试项目(学院多功能防寒服)	判定依据	结论
耐光色牢度	GB/T 31888-2015	合格
耐光、汗复合色牢度	----	----
断裂强力	GB/T 31888-2015	合格
接缝强力	GB/T 31888-2015	合格
顶破强力	----	----
接缝处纱线滑移	GB/T 31888-2015	合格
胀破强力	----	----
起球	GB/T 31888-2015	合格
燃烧性能	----	----
[内胆-填充物]		
pH 值	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
甲醛含量	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
[外套]		
纤维含量	GB/T 29862-2013 GB/T 31888-2015	合格
异味	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
水洗尺寸变化率	GB/T 31888-2015	合格
水洗后扭曲率	GB/T 31888-2015	合格
水洗后外观	GB/T 31888-2015	合格
[外套/内胆]		
附件锐利性	GB/T 31888-2015 GB 31701-2015(B 类)	合格
残留金属针	GB/T 31888-2015 GB 31701-2015(B 类)	合格
绳带	GB 31701-2015(B 类)	合格
[外套-里料]		
pH 值	GB 18401-2010(B 类)	合格



深检(上海)质量技术服务有限公司

SMQ(Shanghai) Quality Technology Service Co., Ltd

地址: 上海市闵行区都园路 2060 号 5 幢 3 楼 312-322 室 电话: 021-52265739

Address: Room 312-322, 3rd Floor, Building 5, 2060 Duyuan Road, Minhang District, Shanghai

扫描下载报告辨真伪



检验检测报告

报告编号: 6260819087

第 5 页, 共 13 页

测试项目(学院多功能防寒服)	判定依据	结论
	GB/T 31888-2015 GB 31701-2015(B 类)	
甲醛含量	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
可分解致癌芳香胺染料	GB 31701-2015(B 类)	合格
耐摩擦色牢度	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
耐汗渍色牢度	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
耐水色牢度	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
耐皂洗色牢度	GB/T 31888-2015	合格
接缝强力	GB/T 31888-2015	合格
接缝处纱线滑移	----	----
[外套-帽子里料]		
pH 值	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
甲醛含量	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
[外套-面料]		
pH 值	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
甲醛含量	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
可分解致癌芳香胺染料	GB 31701-2015(B 类)	合格
耐摩擦色牢度	GB 18401-2010(B 类)	合格

深检(上海)质量技术服务有限公司

SMQ(Shanghai) Quality Technology Service Co., Ltd

地址: 上海市闵行区都园路 2060 号 5 幢 3 楼 312-322 室 电话: 021-52265739

Address: Room 312-322, 3rd Floor, Building 5, 2060 Duyuan Road, Minhang District, Shanghai

扫描下载报告辨真伪



检验检测报告

报告编号: 6260819087

第 6 页, 共 13 页

测试项目(学院多功能防寒服)	判定依据	结论
	GB/T 31888-2015 GB 31701-2015(B 类)	
耐汗渍色牢度	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
耐水色牢度	GB 18401-2010(B 类) GB/T 31888-2015 GB 31701-2015(B 类)	合格
耐皂洗色牢度	GB/T 31888-2015	合格
耐光色牢度	GB/T 31888-2015	合格
耐光、汗复合色牢度	----	----
断裂强力	GB/T 31888-2015	合格
接缝强力	GB/T 31888-2015	合格
顶破强力	----	----
接缝处纱线滑移	GB/T 31888-2015	合格
胀破强力	----	----
起球	GB/T 31888-2015	合格
燃烧性能	----	----



检验检测报告

报告编号: 6260819087

第 7 页, 共 13 页

检 验 项 目	方 法 标 准	标 准 要 求	实 测 结 果	单项结论
【内胆】				
纤维含量（%）	FZ/T 01057.2-2007 FZ/T 01057.3-2007 FZ/T 01057.4-2007	锦纶 100 允差：0	面料 锦纶 100	合格
	FZ/T 01057.2-2007 FZ/T 01057.3-2007 FZ/T 01057.4-2007	锦纶 100 允差：0	里料 锦纶 100	
	FZ/T 01057.2-2007 FZ/T 01057.3-2007 FZ/T 01057.4-2007	聚酯纤维 100 允差：0	填充物 聚酯纤维 100	
异味	GB 18401-2010 6.7	无异味	无	合格
水洗尺寸变化率（%）	GB/T 8628-2013, GB/T 8629-2001, GB/T 8630-2013 5A	长度-2.5~+1.5 领大-1.5~+1.5 胸宽-2.5~+1.5	长度 -0.6 领大 -0.5 胸宽 -0.4	合格
水洗后扭曲率（%）	GB/T 23319.3-2010 方法 B，服装侧面标记法	(上衣、筒裙) ≤ 5.0	0	合格
水洗后外观	GB/T 31888-2015 5.24	变色不低于 4 级；允许轻微的绣花和接缝部位处不平整，允许轻微的面里料缩率不一，不平服；不允许涂层部位脱落、起泡、裂纹，覆粘合衬部位起泡、脱胶，破洞、缝口脱散，附件损坏、明显变色、脱落，不允许其他严重影响服用的外观变化	变色：4-5 级，接缝部位处平整；无破洞、缝口脱散；拉链无损坏、明显变色、脱落；其他无明显异常。	合格
【内胆-领口里料】				
pH 值	GB/T 7573-2009 萃取 介质：KCl 溶液	4.0~8.5	6.7	合格
甲醛含量（mg/kg）	GB/T 2912.1-2009	≤ 75	未检出	合格
	备注：检测结果≤20mg/kg，则报“未检出”。			
【内胆-面料】				

深检(上海)质量技术服务有限公司

SMQ(Shanghai) Quality Technology Service Co., Ltd

地址: 上海市闵行区都园路 2060 号 5 幢 3 楼 312-322 室 电话: 021-52265739

Address: Room 312-322, 3rd Floor, Building 5, 2060 Duyuan Road, Minhang District, Shanghai

扫描下载报告辨真伪



检验检测报告

报告编号: 6260819087

第 8 页, 共 13 页

检 验 项 目	方 法 标 准	标 准 要 求	实 测 结 果	单 项 结 论
pH 值	GB/T 7573-2009 萃取 介质: KCl 溶液	4.0~8.5	6.3	合格
甲醛含量 (mg/kg)	GB/T 2912.1-2009	≤ 75	未检出	合格
	备注: 检测结果≤20mg/kg, 则报“未检出”。			
可分解致癌芳香胺染料 (mg/kg)	GB/T 17592-2024	≤ 20	未检出	合格
	备注: 方法 GB/T 17592-2024 测定低限为 5mg/kg。			
耐摩擦色牢度 (级)	GB/T 3920-2008	干摩擦 ≥ 3-4 湿摩擦 ≥ 3	干摩擦 4-5 湿摩擦 4-5	合格
耐汗渍色牢度 (级)	GB/T 3922-2013	酸性:变色 ≥ 3-4 酸性:沾色 ≥ 3-4 碱性:变色 ≥ 3-4 碱性:沾色 ≥ 3-4	(碱性)(酸性) 变色 4-5 4-5 沾色 -棉 4-5 4-5 -锦纶 4-5 4-5	合格
耐水色牢度 (级)	GB/T 5713-2013	变色 ≥ 3-4 沾色 ≥ 3-4	变色 4-5 沾色 -棉 4-5 -锦纶 4-5	合格
耐皂洗色牢度 (级)	GB/T 3921-2008 A(1)	变色 ≥ 3-4 沾色 ≥ 3-4	变色 4-5 沾色 -棉 4-5 -锦纶 4-5	合格
耐光色牢度 (级)	GB/T 8427-2008 方法 3	≥ 4	>4	合格
耐光、汗复合色牢度	GB/T 14576-2009	--	不适用	--
断裂强力 (N)	GB/T 3923.1-2013	纬向 ≥ 200	纬向 360	合格
接缝强力 (N)	GB/T 13773.1-2008	后袖窿缝 ≥ 140	后袖窿缝 250	合格
顶破强力	GB/T 19976-2005	--	不适用	--
接缝处纱线滑移 (mm)	GB/T 31888-2015 5.21	袖缝 ≤ 6	袖缝 2	合格
胀破强力	GB/T 7742.1-2005 液 压法	--	不适用	--
起球 (级)	GB/T 4802.1-2008 方 法 E	≥ 3-4	4-5	合格
燃烧性能	GB/T 14644-2014	--	不适用	--
【内胆-填充物】				
pH 值	GB/T 7573-2009 萃取	4.0~8.5	7.2	合格

深检(上海)质量技术服务有限公司

SMQ(Shanghai) Quality Technology Service Co., Ltd

地址: 上海市闵行区都园路 2060 号 5 幢 3 楼 312-322 室 电话: 021-52265739

Address: Room 312-322, 3rd Floor, Building 5, 2060 Duyuan Road, Minhang District, Shanghai

扫描下载报告辨真伪



检验检测报告

报告编号: 6260819087

第 9 页, 共 13 页

检 验 项 目	方 法 标 准	标 准 要 求	实 测 结 果	单 项 结 论
	介质: KCl 溶液			
甲醛含量 (mg/kg)	GB/T 2912.1-2009	≤ 75	未检出	合格
	备注: 检测结果≤20mg/kg, 则报“未检出”。			
[外套]				
纤维含量 (%)	FZ/T 01057.2-2007 FZ/T 01057.3-2007 FZ/T 01057.4-2007	聚酯纤维 100 允差: 0	面料 聚酯纤维 100 (薄膜除外)	合格
	FZ/T 01057.2-2007 FZ/T 01057.3-2007 FZ/T 01057.4-2007	聚酯纤维 100 允差: 0	里料 聚酯纤维 100	
异味	GB 18401-2010 6.7	无异味	无	合格
水洗尺寸变化率 (%)	GB/T 8628-2013, GB/T 8629-2001, GB/T 8630-2013 5A	长度-2.5~+1.5 胸宽-2.5~+1.5	长度 -0.4 胸宽 -0.2	合格
水洗后扭曲率 (%)	GB/T 23319.3-2010 方 法 B, 服装侧面标记法	(上衣、筒裙) ≤ 5.0	0	合格
水洗后外观	GB/T 31888-2015 5.24	变色不低于 4 级; 允许 轻微的绣花和接缝部 位处不平整, 允许轻微 的面里料缩率不一, 不 平服; 不允许涂层部位 脱落、起泡、裂纹, 覆 粘合衬部位起泡、脱 胶, 破洞、缝口脱散, 附件损坏、明显变色、 脱落, 不允许其他严重 影响服用的外观变化	变色: 4-5 级, 接缝部位处平整; 面里料无不平服; 无破洞、缝口 脱散; 拉链、子母扣无损坏、明 显变色、脱落; 其他无明显异常。	合格
[外套/内胆]				
附件锐利性	GB/T 31702-2015	不应存在可触及的锐 利尖端和锐利边缘	无可触及性锐利尖端 无可触及性锐利边缘	合格
残留金属针	GB/T 24121-2009	包装上不应使用金属 针等锐利物, 产品上不 允许使用残留金属针	无残留金属针	合格

深检(上海)质量技术服务有限公司

SMQ(Shanghai) Quality Technology Service Co., Ltd

地址: 上海市闵行区都园路 2060 号 5 幢 3 楼 312-322 室 电话: 021-52265739

Address: Room 312-322, 3rd Floor, Building 5, 2060 Duyuan Road, Minhang District, Shanghai

扫描下载报告辨真伪



检验检测报告

报告编号: 6260819087

第 10 页, 共 13 页

检 验 项 目	方 法 标 准	标 准 要 求	实 测 结 果	单 项 结 论
		等锐利物		
绳带	GB 31701-2015 5.7	应符合条款 4.4.3	符合	合格
【外套-里料】				
pH 值	GB/T 7573-2009 萃取 介质：KCl 溶液	4.0~8.5	6.8	合格
甲醛含量（mg/kg）	GB/T 2912.1-2009	≤ 75	未检出	合格
	备注：检测结果≤20mg/kg，则报“未检出”。			
可分解致癌芳香胺染料（mg/kg）	GB/T 17592-2024	≤ 20	未检出	合格
	备注：方法 GB/T 17592-2024 测定低限为 5mg/kg。			
耐摩擦色牢度（级）	GB/T 3920-2008	干摩擦 ≥ 3-4 湿摩擦 ≥ 3	干摩擦 4-5 湿摩擦 4-5	合格
耐汗渍色牢度（级）	GB/T 3922-2013	酸性:变色 ≥ 3-4 酸性:沾色 ≥ 3-4 碱性:变色 ≥ 3-4 碱性:沾色 ≥ 3-4	(碱性)(酸性) 变色 4-5 4-5 沾色 -棉 4-5 4-5 -聚酯纤维 4-5 4-5	合格
耐水色牢度（级）	GB/T 5713-2013	变色 ≥ 3-4 沾色 ≥ 3-4	变色 4-5 沾色 -棉 4-5 -聚酯纤维 4-5	合格
耐皂洗色牢度（级）	GB/T 3921-2008 A(1)	变色 ≥ 3-4 沾色 ≥ 3-4	变色 4-5 沾色 -棉 4-5 -聚酯纤维 4-5	合格
接缝强力（N）	GB/T 13773.1-2008	后袖窿缝 ≥ 80	后袖窿缝 240	合格
接缝处纱线滑移	GB/T 31888-2015 5.21	--	不适用	--
【外套-帽子里料】				
pH 值	GB/T 7573-2009 萃取 介质：KCl 溶液	4.0~8.5	6.5	合格
甲醛含量（mg/kg）	GB/T 2912.1-2009	≤ 75	未检出	合格
	备注：检测结果≤20mg/kg，则报“未检出”。			
【外套-面料】				
pH 值	GB/T 7573-2009 萃取 介质：KCl 溶液	4.0~8.5	6.4	合格
甲醛含量（mg/kg）	GB/T 2912.1-2009	≤ 75	未检出	合格

深检(上海)质量技术服务有限公司

SMQ(Shanghai) Quality Technology Service Co., Ltd

地址: 上海市闵行区都园路 2060 号 5 幢 3 楼 312-322 室 电话: 021-52265739

Address: Room 312-322, 3rd Floor, Building 5, 2060 Duyuan Road, Minhang District, Shanghai

扫描下载报告辨真伪



检验检测报告

报告编号: 6260819087

第 11 页, 共 13 页

检 验 项 目	方 法 标 准	标 准 要 求	实 测 结 果	单 项 结 论
	备注：检测结果≤20mg/kg，则报“未检出”。			
可分解致癌芳香胺染料（mg/kg）	GB/T 17592-2024	≤ 20	未检出	合格
	备注：方法 GB/T 17592-2024 测定低限为 5mg/kg。			
耐摩擦色牢度（级）	GB/T 3920-2008	干摩擦 ≥ 3-4 湿摩擦 ≥ 3	干摩擦 4-5 湿摩擦 4-5	合格
耐汗渍色牢度（级）	GB/T 3922-2013	酸性:变色 ≥ 3-4 酸性:沾色 ≥ 3-4 碱性:变色 ≥ 3-4 碱性:沾色 ≥ 3-4	(碱性)(酸性) 变色 4-5 4-5 沾色 -棉 4-5 4-5 -聚酯纤维 4-5 4-5	合格
耐水色牢度（级）	GB/T 5713-2013	变色 ≥ 3-4 沾色 ≥ 3-4	变色 4-5 沾色 -棉 4-5 -聚酯纤维 4-5	合格
耐皂洗色牢度（级）	GB/T 3921-2008 A(1)	变色 ≥ 3-4 沾色 ≥ 3-4	变色 4-5 沾色 -棉 4-5 -聚酯纤维 4-5	合格
耐光色牢度（级）	GB/T 8427-2008 方法 3	≥ 4	>4	合格
耐光、汗复合色牢度	GB/T 14576-2009	--	不适用	--
断裂强力（N）	GB/T 3923.1-2013	经向 ≥ 200 纬向 ≥ 200	经向 630 纬向 630	合格
接缝强力（N）	GB/T 13773.1-2008	后袖窿缝 ≥ 140	后袖窿缝 250	合格
顶破强力	GB/T 19976-2005	--	不适用	--
接缝处纱线滑移（mm）	GB/T 31888-2015 5.21	袖缝 ≤ 6	袖缝 3	合格
胀破强力	GB/T 7742.1-2005 液 压法	--	不适用	--
起球（级）	GB/T 4802.1-2008 方 法 E	≥ 3-4	4-5	合格
燃烧性能	GB/T 14644-2014	--	不适用	--
备注	1. “未检出”指小于报告限。 2. 标记“-”的测试项目表示不予判定或不具备判定条件。 3. 除非客户要求，本报告检测结果及符合性判定不考虑测量结果的不确定度。 4. 可分解致癌芳香胺染料分包深检集团（浙江）质量技术服务有限公司(221120113084)。			

深检(上海)质量技术服务有限公司

SMQ(Shanghai) Quality Technology Service Co., Ltd

地址: 上海市闵行区都园路 2060 号 5 幢 3 楼 312-322 室 电话: 021-52265739

Address: Room 312-322, 3rd Floor, Building 5, 2060 Duyuan Road, Minhang District, Shanghai

扫描下载报告辨真伪



检验检测报告

报告编号: 6260819087

第 12 页, 共 13 页

注: 可分解致癌芳香胺染料

No. (编号)	CAS No. (化学文摘编号)	Forbidden Arylamine (化学名称)
1	92-67-1	4-aminobiphenyl (4-氨基联苯)
2	92-87-5	benzidine (联苯胺)
3	95-69-2	4-chloro-o-toluidine (4-氯邻甲苯胺)
4	91-59-8	2-naphthylamine (2-萘胺)
5	97-56-3	o-aminoazotoluene (邻氨基偶氮甲苯)
6	99-55-8	5-nitro-o-toluidine (5-硝基-邻甲苯胺)
7	106-47-8	p-chloroaniline (对氯苯胺)
8	615-05-4	2,4-diaminoanisole (2,4-二氨基苯甲醚)
9	101-77-9	4,4'-diaminobiphenylmethane (4,4'-二氨基二苯甲烷)
10	91-94-1	3,3'-dichlorobenzidine (3,3'-二氯联苯胺)
11	119-90-4	3,3'-dimethoxybenzidine (3,3'-二甲氧基联苯胺)
12	119-93-7	3,3'-dimethylbenzidine (3,3'-二甲基联苯胺)
13	838-88-0	3,3'-dimethyl-4,4'-diaminobiphenylmethane (3,3'-二甲基-4,4'-二氨基二苯甲烷)
14	120-71-8	p-cresidine (2-甲氧基-5-甲基苯胺)
15	101-14-4	4,4'-methylene-bis- (2-chloroaniline) (4,4'-亚甲基-二- (2-氯苯胺))
16	101-80-4	4,4'-oxydianiline (4,4'-二氨基二苯醚)
17	139-65-1	4,4'-thiodianiline (4,4'-二氨基二苯硫醚)
18	95-53-4	o-toluidine (邻甲苯胺)
19	95-80-7	2,4-toluylenediamine (2,4-二氨基甲苯)
20	137-17-7	2,4,5-trimethylaniline (2,4,5-三甲基苯胺)
21	90-04-0	o-anisidine (邻氨基苯甲醚)
22	60-09-3	4-aminoazobenzene (4-氨基偶氮苯)
23	95-68-1	2,4-xylydine (2,4-二甲基苯胺)
24	87-62-7	2,6-xylydine (2,6-二甲基苯胺)
备注:	注 1: 邻氨基偶氮甲苯 (CAS No.97-56-3)、5-硝基-邻甲苯胺/2-氨基-4 硝基甲苯 (CAS No.99-55-8) 经本方法处理后进行样检测分解为邻甲苯胺和 2, 4-二氨基甲苯。 注 2: 苯胺 (CAS No.62-53-3) 特征离子为 93amu, 1,4-苯二胺 (CAS No.106-50-3) 特征离子为 108amu. 4-氨基偶氮苯经本方法检测分解为苯胺和/或 1,4-苯二胺, 如检测到苯胺和/或 1,4-苯二胺, 应重新按照 GB/T 23344 进行测试。 注 3: 试样前处理方法: 直接还原处理。	



检验检测报告

报告编号: 6260819087

第 13 页, 共 13 页

检测报告附页

样品图片



----- 报告结束 -----



深检(上海)质量技术服务有限公司

SMQ(Shanghai) Quality Technology Service Co., Ltd

地址: 上海市闵行区都园路 2060 号 5 幢 3 楼 312-322 室 电话: 021-52265739

Address: Room 312-322, 3rd Floor, Building 5, 2060 Duyuan Road, Minhang District, Shanghai

扫描下载报告辨真伪



重要声明

Important statement

1. 本公司保证检验检测的科学性,对检验检测的数据负责,并对委托单位所提供的样品和技术资料保密。
The company is committed to assuring the scientificness impartiality and accuracy of all tests carried out, responsibility for test data gained, and keeping confidential of all test samples and technical documents provided.

2. 抽样按照本公司程序文件《抽样程序》和相应产品的检验检测细则的规定执行。

The sampling should be carried out according to the "sampling procedure" defined in the Procedure Document and relevant testing specifications.

3. 报告无批准人签字,或涂改,或未盖本公司报告专用章及骑缝章无效。未经本公司许可,不得部分复印、摘用或篡改本报告内容。复印报告未重新加盖本公司报告专用章无效。

Any report/certificate having not been signed by authorized approver, or having been altered without authorization, or without both the Dedicated Report/Certificate Seal and its across-page seal is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report/certificate is not permitted without the written authorization of the company. Any copy of certificates/reports without the Dedicated Report/Certificate Seal is deemed to be invalid.

4. 送样委托检验检测结果仅对来样有效:委托检验检测的样品信息及委托方信息均由委托方提供,本公司不对其真实性及准确性负责。

The test results presented in the report apply only to the tested sample. The product information and the applicant information are provided by the customer and the company assumes no responsibility for their validity and accuracy.

5. 未经公司同意,样品委托人请勿使用检验检测结果进行不当宣传。

Any use of the company test result for advertisement of the tested material or product must be approved in writing by the company.

6. 无认可认定标志的报告,仅作科研、教学或内部质量控制等用途之用。

Reports without accreditation marks are only used for scientific research, teaching or internal quality control purposes.

7. 委托方对报告有异议的,应于报告发出之日起十五日内向本公司提出。政府行政管理部门下达的监督检验任务,受检方对报告有异议的,应按政府行政管理部门文件规定及国家相关法律、法规处理。

Objection to report/certificate issued by the company should be submitted to the company within 15 days after the issuance of the test. The mandatory inspection assigned by government administrative departments shall be carried out in accordance with the documents and regulations of the government administrative department and relevant national laws and regulations if inspected parties raise any objection to the inspection.

8. 报告更改后,发出的电子版报告、报告的扫描件及传真件若无法追回,则委托方有义务将更改后的报告提供给使用原报告的相关方。

The company is not responsible for recalling the electronic version of the original report/certificate when any revision is made to them. The applicant assumes the responsibility of providing the revised version to any interested party who uses them.

9. 只申领电子报告时,相关内容和效力以电子报告为准;电子报告和纸质报告同时申领时,电子报告仅作为纸质报告的副本,相关内容和效力以同编号纸质报告为准。

The relevant content and effectiveness is subject to the electronic version of the original report which was only applied for. When an electronic report and a paper report are applied for at the same time, the electronic report is only a copy of the paper report, and the relevant content and effectiveness is subject to the paper report.

10. 检验报告二维码具浏览和下载完整报告功能,是应委托方要求所设,该二维码及其复制图能使任何人扫描获取完整的检验报告电子版,本报告持有人如需限制他人经该二维码获取检验报告内容,应自行遮盖或消除检验报告及其复制件所附二维码,我司对委托方选择检验报告二维码功能所致的信息泄露概不负责(适用于附二维码报告)。

The QR code has the function of browsing and downloading complete report. Setting this function or not is chosen by the customer. The QR code and its copy enable anyone to scan and obtain the complete electronic version of the test report. Thus, if the owner of this report needs to restrict others from obtaining the content of the test report through the QR code, he shall cover or remove the QR code attached to the test report and its copies by himself. SMQ assumes no responsibility for the information leakage caused by the customers selection of the QR code function of the test report (This clause applies to reports with QR code attached).

投诉及报告/证书真伪查询电话

Complaint hotline: 021-52265739